Round Sling Polyester - Heavy-Lift

Product information



Heavy lift polyester round slings by Lift-Tex® are designed for demanding lifting operations where durability and controlled handling are required. The polyester yarn core is protected by a herringbone-woven sleeve, providing increased resistance to abrasion and edge contact. These slings are suitable for general heavy lifting where robust textile solutions are preferred.

When to choose this product

Best for:

- General heavy lifting with risk of abrasion or edge contact
- Applications requiring flexible slings with predictable handling

Product benefits

- Herringbone polyester sleeve improves resistance to abrasion and edges
- Flexible construction supports easy positioning and load handling
- Small length tolerances enable more accurate lift planning
- RFID options support inspection routines and traceability

Extra protection on demand. The use of (extra) appropriate protections is always recommended on the bearing points.

... *Read more*

Material: Polyester
Marking: According to standard, CE-mark, manufacturer's symbol, working load limit (WLL), length, and a label with handling instruction.
Temperature range: -40°C up to +100°C.
Standard: EN 1492-2
Note: Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

Safety factor: 7:1

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

Round Sling Polyester - Heavy-Lift

Lifting table

Part code	Diameter mm	WLL ton	Colour
340101200000291	43	12	Orange
340101500000291	47	15	Orange
340102000000291	55	20	Orange
340102500000291	60	25	Orange
340103000000291	65	30	Orange
340104000000291	75	40	Orange
340105000000291	85	50	Orange
340106000000291	95	60	Orange
340107000000291	100	70	Orange
340108000000291	110	80	Orange
340108500000291	115	85	Orange
340109000000291	120	90	Orange
340110000000291	140	100	Orange
340112500000291	160	125	Orange
340115000000291	180	150	Orange
340117500000291	210	175	Orange
340118000000291	230	180	Orange
340120000000291	240	200	Orange

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved