

ELD 168 Swivel hook (underload-light duty)



Product information

Suitable for turning under load. Hook with standard bearings for the most common applications.

Material: Grade 8.

Marking: According to standard

Finish: Red painted.

Standard: EN 1677-2

Note: Can rotate with load.

Safety factor: 4:1.

Grade: 8

Part Code	Code	WLL ton	chain Ø mm	A mm	B mm	C mm	D mm	D1 mm	E mm	F mm	H mm	L mm	M mm	N mm	P mm	R mm	Weight kg	Delivery time
420500130770	168010 ES	1.25	6	10	34	77	24	20	21	15	31	133	38	63	39	12,5	0.75	5
420500160770	168015 ES	1.6	7	10	33	82	26	22	23	18	34	140	38	63	39	12,5	1	10
420500250770	168020 ES	2.5	8	12,5	42	94	27	23	27	23	38	163	47	79	48	16	1.4	10
420500320770	168030 ES	3.2	10	12,5	40	106	32	27	31	23	42	172	47	79	48	16	1.66	5
420500540770	168045 ES	5.4	13	15	50	132	40	35	37	30	50	213	58	96	60	19	3.65	10
420500800770	168110 ES	8	16	17,5	65	165	51	43	49	37	62	266	72	120	70	24	5.87	10
420501150770	168150 ES	11.5	19	22	68	198	58	53	60	43	75	310	82	136	82	27	9.75	10
420501600770	168150 ES	16	22	24	84	222	66	58	67	52	84	352	92	154	92	31	15.3	10
420502200770	168200 ES	22	26	29	107	283	87	78	80	64	110	434	115	191	108	38	26.5	10
420503150770	168300 ES	31.5	32	34	117	339	97	87	94	80	120	512	132	222	132	45	50	10

Blueprint

