ELD 168 Swivel hook (underload-light duty)

Product information

Suitable for turning under load. Hook with standard bearings for the most common applications.

... *Read more*



Marking: According to standard, CE-mark
Finish: Red painted.
Standard: EN 1677-2
Note: Can rotate with load.


Safety factor: 4:1.
Grade: 8

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

ELD 168 Swivel hook (underload-light duty)

Blueprint



Lifting table

Part code	Code	Chain diameter mm	WLL ton	EWL mm	Weight kg
420500130770	168 010 ES	6	1.25	133	0.75
420500160770	168 015 ES	7	1.6	140	1
420500250770	168 020 ES	8	2.5	163	1.4
420500320770	168 030 ES	10	3.2	172	1.66
420500540770	168 045 ES	13	5.4	213	3.65
420500800770	168 070 ES	16	8	266	5.87
420501150770	168 110 ES	19	11.5	310	9.75
420501600770	168 150 ES	22	16	352	15.3
420502200770	168 200 ES	26	22	434	26.5
420503150770	168 300 ES	32	31.5	512	50

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved