


Truck crane



Jib crane



Overhead cranes



## Steel Wire Rope ROPETEX S18

### Product information

**ROPETEX**



ROPETEX S18 is a semi-rotation resistant steel wire rope consisting of two layers of strands and a (steel) wire strand core. As the outer strands are closed in the opposite direction of the inner strands this rope is considered as semi-rotation resistant rope.

ROPETEX S18 should not be used with a swivel and for unguided single part in great lifting height, with reference to the rotational properties (see manual).

ROPETEX S18 is mostly used in diameter from 3 to 8 mm in several lifting applications like truck cranes, overhead cranes, jib cranes, electrical hoists and all other applications where a semi-rotation resistant wire rope is good enough.

If you are searching for a rotation-resistant steel wire rope, look at ROPETEX S55.

**Rope construction:** 18x7-WSC

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C, for operating temperatures between 100°C and 200°C reduce MBF by minus 10 %

**Standard:** EN 12385-4

**Note:** Ropes of the class 35x7 have to be replaced always by ropes of the same/comparable class and never by ropes of class 18x7. Whereas ropes of the class 18x7 can be replaced also by ropes of 35x7 from a technical point of view.

**Fill factor:** 0,55

**RCN:** 23-1

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
102100304270011	3	1,960	Galvanized	sZ	5.79	3.9	A-1	3.61
102100404270011	4	1,960	Galvanized	sZ	10.3	6.9	A-1	6.42
102100504270011	5	1,960	Galvanized	sZ	16.1	10.8	A-1	10
102100604270011	6	1,960	Galvanized	sZ	23.1	15.6	A-1	14.4
102100704270011	7	1,960	Galvanized	sZ	31.5	21.2	A-1	19.6
102100804270011	8	1,960	Galvanized	sZ	41.1	27.7	A-1	25.7