Connecting Link Pewag CWP connex

Product information



Universal connecting link consisting of two die-forged identical halves, a bolt and a safety sleeve.

... *Read more*

Material: Alloy steel
Marking: According to standard, CE-mark, Pewag or PW, winner pro or 12, H16, batch code and type.
Temperature range: -60ºC up to +300ºC.
Finish: Light blue powdercoated.
Standard: EN 1677-1
Warning: Not to be heat-treated.


Safety factor: 4:1
Grade: 12

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Connecting Link Pewag CWP connex

Blueprint



Lifting table

Part code	Code	Chain diameter mm	WLL ton	b mm	c mm	d mm	e mm	g mm	s mm	t mm	Weight kg
403200240020	CWP 7	7	2.36	51	11.5	9	63	17	13	15.5	0.24
403200300020	CWP 8	8	3	58	14	10	62	20	15	20	0.27
403200500020	CWP 10	10	5	66	18	13	78	22	21	25	0.57
403200800020	CWP 13	13	8	84	22	17	107	25	25	34	1.43
403201250020	CWP 16	16	12.5	120	27	21	128	48	31	41	2.26

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved