

Connecting Link Pewag CWP connex

Product information



Universal connecting link consisting of two die-forged identical halves, a bolt and a safety sleeve.

... [Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

Temperature range: -60°C up to +300°C.

Finish: Light blue powdercoated.

Standard: EN 1677-1

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 12

Connecting Link Pewag CWP connex

Blueprint



Lifting table

| Part code | Code | Chain diameter mm | WLL ton | b mm mm | c mm | d mm mm | e mm mm | g mm mm | s mm mm | t mm | Weight kg |
|--------------|--------|-------------------|---------|---------|------|---------|---------|---------|---------|------|-----------|
| 403200240020 | CWP 7 | 7 | 2.36 | 51 | 11.5 | 9 | 63 | 17 | 13 | 15.5 | 0.24 |
| 403200300020 | CWP 8 | 8 | 3 | 58 | 14 | 10 | 62 | 20 | 15 | 20 | 0.27 |
| 403200500020 | CWP 10 | 10 | 5 | 66 | 18 | 13 | 78 | 22 | 21 | 25 | 0.57 |
| 403200800020 | CWP 13 | 13 | 8 | 84 | 22 | 17 | 107 | 25 | 25 | 34 | 1.43 |
| 403201250020 | CWP 16 | 16 | 12.5 | 120 | 27 | 21 | 128 | 48 | 31 | 41 | 2.26 |