# Grab Hook Pewag PWP

**Product information**



Application for shortening of chain and chain slings that must not tighten ... *Read more*


**Material:** Alloy steel
**Marking:** According to standard, CE-mark, Pewag or PW, winner pro or 12, H16, batch code and type.
**Temperature range:** -60ºC up to +300ºC.
**Finish:** Light blue powdercoated.
**Standard:** EN 1677-1
**Warning:** Not to be heat-treated.

**Safety factor:** 4:1
**Grade:** 12

**CERTEX Svenska AB**
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved

# Grab Hook Pewag PWP

## Blueprint




## Lifting table

| Part code | Code | WLL ton | EWL mm | For chain Ø mm | b mm | d1 mm | d2 mm | e mm | g1mm mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|
| 403300300020 | PWP 7/8 | 3 | 68 | 7-8 | 63 | 18 | 11 | 68 | 10 | 0.51 |
| 403300500020 | PWP 10 | 5 | 88 | 10 | 81 | 22 | 14 | 88 | 13 | 1.04 |
| 403300800020 | PWP 13 | 8 | 110 | 13 | 103 | 26 | 18 | 110 | 17 | 2.19 |

**CERTEX Svenska AB**
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved