



Lever Hoist POWERTEX PLH-S1

Product information

POWERTEX



Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Durable all steel construction with powder coated finish and plated frame components.
- Safe, well covered automatic load reaction brake.
- European made COROLIM® protected load chain.
- Corrosion resistance of the chain is equivalent to ISO944-9 C5High / ISO9223 C3
- Bottom hook with ball bearing.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manuals.
- User manuals in 14 languages included.
- Testcertificate enclosed.

Marking: According to standard, CE-marked

Temperature range: -10°C up to +50°C.

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Part code	WLL ton	Lifting height m	Number of falls	A mm	B mm	C mm	D mm	E mm	H min mm	Ø mm	Weight kg	Delivery time
500500050150090	0.5	1.5	1	150	90	118	253	22	280	20	5.3	5
500500100300090	1	3	1	156	95	138	278	26	330	25	8.1	10
500500100150090	1	1.5	1	156	95	138	278	25	330	26	8.1	5

Blueprint

