

Chain Block POWERTEX PCB-S1

Product information



POWERTEX

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Durable all steel construction with powder coated finish and plated frame components.
- Safe, well covered automatic load reaction brake.
- Sealed ball bearings on the chain wheel maximise efficiency and serviceability.
- European made COROLIM® protected load chain.
- Corrosion resistance of the chain is equivalent to ISO944-9 C5High / ISO9223 C3
- Bottom hook with ball bearing.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manuals.
- User manuals in 14 languages included.
- Fulfills the Machinery Directive 2006/42/EC.
- Comply fully with the EN norms 13157 and 818-7.
- Testcertificate enclosed.

... [Read more](#)

Marking: According to standard, CE-marked

Temperature range: -10°C up to +50°C.


Standard: EN 13157, EN 818-7

Warning: Do not overload the brake by prolonged lowering. It may cause brake function to fail.

Safety factor: 4:1

Chain Block POWERTEX PCB-S1

Blueprint



Lifting table

Part code	WLL ton	Lifting height m	Number of falls	Load chain mm	A mm	B mm	C mm	Ø mm mm	E mm	H mm	Weight kg
500100030300070	0.25	3	1	4 x 12	106	68	108	18	20	280	6.4
500100300600070	3	6	1	10 x 30	195	95	226	36	37	435	29.4