# ROPETEX Ultra Lube 2

**Product information**




ROPETEX

Ropetex Ultra Lube 2 is an ecofriendly, advanced high-performance hybrid grease. It is developed to perform in dockside, offshore and deep-water environments. Furthermore, it has superior wash-off performance and is bio-degradable, non-toxic and non-bio accumulative.

Ropetex Ultra Lube 2 is an **E**nvironmentally **A**cceptable **L**ubricant (EAL) and is fully VGP
2013 compliant. It can therefore be used on docksides, riversides, lakes and other environmental sensitive locations.

Due to the composition of the product, it is stable over a wide temperature range, making it suitable for tropical environments.

**Typical applications**: Offshore cranes, dockside cranes, Offshore-, harbor- and subsea installations.

**Application methods:** High pressure equipment or brushing.

**Minimum application temperature**: -5°C (Product should be kept to at least 10°C for 48 hours before application).

**Color/texture:** Matte black grease

**NLGI grade:** 2

**Drop point:** 154°C

**Break point:** -60°C

**Relative density:** 0.9 - 0.95

**Hot salt spray test:** 2,880 hours

**4-ball weld load:** > 400 kgf

**4-ball weld scar**: 0.55 mm

**Water spray-off:** < 60% retention

**Environmentally Acceptable Lubricant:** YES

... *Read more*

**Temperature range:** -40°C up to +120°C

**CERTEX Svenska AB**
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

# ROPETEX Ultra Lube 2

## Lifting table

| Part code | Description | Weight kg |
|---|---|---|
| 142501250050 | Ropetex Ultra Lube 2 | 12.5 |

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved