


Fast Connector Socket FCS - with bolt



Product information



Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Can be used to terminate all constructions of wire rope including high performance ropes, anti-rotation ropes and standard 6 strand ropes.

The connector has to be moulded/casted on the steel wire rope with wirelock resin.

Features: Designed for use with mobile cranes.

Material: Quenched and tempered cast steel.

Finish: Blue painted (P) or hot dip galvanized (G).

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Part Code	Code	Rope diameter mm	MBL T	Finish	TB mm	TL mm	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	Weight	Total price
01-7015013B	FCS 701 B	11-13	20	Painted	80	150	62	61	27	15	25	12	25	50	33	49	46	1.6	N/A
01-7015016B	FCS 702 B	13-16	25	Painted	96	182	72	78	32	18	30	14	32	58	38	60	59	2.6	N/A
01-7015019B	FCS 703 B	16-19	40	Painted	107	218	85	93	40	21	35	16	38	70	45	70	69	4.5	N/A
01-7015023B	FCS 704 B	20-22	55	Painted	123	253	102	106	45	24	41	19	44	80	50	82	81	6.5	N/A
01-7015026B	FCS 705 B	23-26	75	Painted	138	298	115	123	60	28	51	22	51	104	60	95	90	11	N/A
01-7015029B	FCS 706 B	27-29	90	Painted	160	357	140	152	65	32	57	25	57	114	70	107	116	16	N/A

Blueprint

