










Belastningstabell

Textila redskap










Rundsling polyester

enligt EN 1492-2

Säkerhetsfaktor 7:1		1-part	U-lyft	Snarat	U-form i vinkel		2-part sling		3- och 4-part sling		
											
					0°- 45°	45°-60°	0°- 45°	45°-60°	0°- 45°	45°- 60°	
		Max last (WLL) i ton									
	Färg	Violett	1,0	2,0	0,8	1,4	1,0	1,4	1,0	2,1	1,5
	Grön	2,0	4,0	1,6	2,8	2,0	2,8	2,0	4,2	3,0	
	Gul	3,0	6,0	2,4	4,2	3,0	4,2	3,0	6,3	4,5	
	Grå	4,0	8,0	3,2	5,6	4,0	5,6	4,0	8,4	6,0	
	Röd	5,0	10,0	4,0	7,0	5,0	7,0	5,0	10,5	7,5	
	Brun	6,0	12,0	4,8	8,4	6,0	8,4	6,0	12,6	9,0	
Blå	8,0	16,0	6,4	11,2	8,0	11,2	8,0	16,8	12,0		
Orange	10,0	20,0	8,0	14,0	10,0	14,0	10,0	21,0	15,0		
Orange	12,0	24,0	9,6	16,8	12,0	16,8	12,0	25,2	18,0		
Orange	15,0	30,0	12,0	21,0	15,0	21,0	15,0	31,5	22,5		
Orange	20,0	40,0	16,0	28,0	20,0	28,0	20,0	42,0	30,0		
Faktor (K _L)		1	2	0,8	1,4	1	1,4	1	2,1	1,5	

Bandstroppar och bandsling polyester

enligt EN 1492-1

Säkerhetsfaktor 7:1		1-part	U-lyft	Snarat	U-form i vinkel		2-part sling		3- och 4-part sling		
											
					0°- 45°	45°-60°	0°- 45°	45°-60°	0°- 45°	45°- 60°	
		Max last (WLL) i ton									
	Bredd	50 mm	1,0	2,0	0,8	1,4	1,0	1,4	1,0	2,1	1,5
	60 mm	2,0	4,0	1,6	2,8	2,0	2,8	2,0	4,2	3,0	
	90 mm	3,0	6,0	2,4	4,2	3,0	4,2	3,0	6,3	4,5	
	120 mm	4,0	8,0	3,2	5,6	4,0	5,6	4,0	8,4	6,0	
	150 mm	5,0	10,0	4,0	7,0	5,0	7,0	5,0	10,5	7,5	
	180 mm	6,0	12,0	4,8	8,4	6,0	8,4	6,0	12,6	9,0	
240 mm	8,0	16,0	6,4	11,2	8,0	11,2	8,0	16,8	12,0		
300 mm	10,0	20,0	8,0	14,0	10,0	14,0	10,0	21,0	15,0		
Faktor (K _L)		1	2	0,8	1,4	1	1,4	1	2,1	1,5	