

Kätting HLZ klass 2 - halvlånglänkad

Produktinformation



Allmänt: Kätting avsedd för diverse ändamål.

Standard: SMS 1503.

Material: Klass 2.

Ytbehandling: 3-4,5 mm elförzinkad, 5- mm varmförzinkad.

Klass: 2



Art.nr	Kätting Ø mm	Min brottkraft kN	Längd m	D mm	E mm	H mm	Vikt kg/m	Totalt pris
11.601503020E	2	1,5	25	2	15	3	0,07	N/A
11.601503025E	2,5	2,3	25	2,5	17	4	0,11	N/A
11.601503030E	3	3,4	25	3	19	5	0,16	N/A
11.601503035E	3,5	4,6	25	3,5	21	5,5	0,22	N/A
11.601503040E	4	6	25	4	23	6	0,28	N/A
11.601503045E	4,5	7,5	25	4,5	25	7	0,36	N/A
11.601503050G	5	9,5	25	5	28	8	0,45	N/A
11.601503055G	5,5	11,5	25	5,5	31	9	0,5	N/A
11.601503060G	6	13,5	25	6	35	10	0,6	N/A
11.601503070G	7	18,5	25	7	41	11	0,9	N/A
11.601503080G	8	24	25	8	47	13	1,1	N/A
11.601503090G	9	32	25	9	53	15	1,4	N/A
11.601503100G	10	40	25	10	59	16	1,7	N/A
11.601503110G	11	46	25	11	50	15	2,2	N/A
11.601503130G	13	63	25	13	55	20	3	N/A
11.601503160G	16	96	25	16	65	22	4,6	N/A

Ritning & mått

