

## INDIROPE 6xK26WS-IWRC

### Produktinformation



NO PICTURE

6xK26WS - IWRC is a unique construction of steel wire rope, designed for use with the majority of pulling machines and winches this construction has a independant wire rope core (IWRC) and is of a compacted design to ensure smother running through a pulling machine and around pullys. These properties also make it ideal as a heavier duty Zip Wire, suitable for commercial applications.

#### SPECIFICATIONS

- Holds up extremely well to rough; rugged use
- Higher linear density
- Made from extra improved plow steel (EIPS) with an independent wire rope center (IWRC)

RCN: 06

| Art.nr          | Lindiameter<br>mm | Tråd hållfasthet<br>N/mm <sup>2</sup> | Ytbehandling | Rope lay | Min brottkraft<br>kN | Stålarea<br>mm <sup>2</sup> | Smörjning | Vikt<br>kg/100m |
|-----------------|-------------------|---------------------------------------|--------------|----------|----------------------|-----------------------------|-----------|-----------------|
| 103101004091000 | 10                | 2 060                                 | Blank        | sZ       | 104                  | -                           | Dry       | -               |
| 103101104091000 | 11                | 2 060                                 | Blank        | sZ       | 123                  | -                           | Dry       | -               |
| 103101204091000 | 12                | 2 060                                 | Blank        | sZ       | 144                  | -                           | Dry       | -               |
| 103101304091000 | 13                | 2 060                                 | Blank        | sZ       | 165                  | -                           | Dry       | -               |
| 103101404091000 | 14                | 2 060                                 | Blank        | sZ       | 188                  | -                           | Dry       | -               |