

Lyrschackel 750-S Rostfri

Produktinformation

Utförande: Smidd.

... [Read more](#)



Material: Rostfritt syrafast stål AISI 316.


Märkning: CE-märkning

Ytbehandling: Polerad.

Säkerhetsfaktor: 6:1

Lyrschackel 750-S Rostfri

Ritning & mått



Lyfttabell

| Art.nr | Max last (WLL) ton | Gänga | a mm | c mm | d mm | d1 mm | e mm | d2 mm mm | Vikt kg |
|--------------|-----------------------|-------|------|------|------|-------|------|----------|------------|
| 420100040100 | 0,4 | M8 | 16 | 30 | 8 | M8 | 23 | 16 | 0,05 |
| 420100060100 | 0,6 | M10 | 20 | 40 | 10 | M10 | 27 | 20 | 0,115 |
| 420100090100 | 0,9 | M12 | 25 | 47 | 12 | M12 | 37 | 26 | 0,213 |
| 420100150100 | 1,5 | M16 | 25 | 50 | 13 | M16 | 34 | 33 | 0,34 |
| 420100250100 | 2,5 | M20 | 28 | 60 | 16 | M20 | 42 | 40 | 0,601 |
| 420100300100 | 3 | M22 | 31 | 71 | 19 | M22 | 51 | 48 | 0,977 |