

## Stållina 8x36WS-IWRC

### Produktinformation



**Konstruktion:** 8x36WS-IWRC (337-trådig)

**Märkning:** Enligt standard

**Standard:** EN 12385-4


**Fyllnadsfaktor:** 0.6

**RCN:** 11

Vinschlina



Telfer/ Travers



Tornkran



Art.nr	Lindiameter	Trådållfasthet N/mm <sup>2</sup>	Ytbehandling	Rope lay	Min brottkraft kN	Stålarea mm <sup>2</sup>	Smörjning	Vikt kg/100m
101101304070091	13	1 960	Blank	sZ	118	79,1	A-1	70,5
101101303070091	13	1 960	Blank	zS	118	79,1	A-1	70,5
101101304270091	13	1 960	Galvaniserad	sZ	118	79,1	A-1	70,5
101101303270091	13	1 960	Galvaniserad	zS	118	79,1	A-1	70,5

101101404050091	14	1 770	Blank	sZ	124	91,7	A-1	81,7
101101404070091	14	1 960	Blank	sZ	137	91,7	A-1	81,7
101101403070091	14	1 960	Blank	zS	137	91,7	A-1	81,7
101101404270091	14	1 960	Galvaniserad	sZ	137	91,7	A-1	81,7
101101403270091	14	1 960	Galvaniserad	zS	137	91,7	A-1	81,7
101101604070091	16	1 960	Blank	sZ	179	120	A-1	107
101101603070091	16	1 960	Blank	zS	179	120	A-1	107
101101604270091	16	1 960	Galvaniserad	sZ	179	120	A-1	107
101101603270091	16	1 960	Galvaniserad	zS	179	120	A-1	107
101101804070091	18	1 960	Blank	sZ	226	152	A-1	135
101101803070091	18	1 960	Blank	zS	226	152	A-1	135
101101804270091	18	1 960	Galvaniserad	sZ	226	152	A-1	135
101101803270091	18	1 960	Galvaniserad	zS	226	152	A-1	135
101102004070091	20	1 960	Blank	sZ	279	187	A-1	167
101102003070091	20	1 960	Blank	zS	279	187	A-1	167
101102004270091	20	1 960	Galvaniserad	sZ	279	187	A-1	167
101102003270091	20	1 960	Galvaniserad	zS	279	187	A-1	167
101102204070091	22	1 960	Blank	sZ	338	227	A-1	202
101102203070091	22	1 960	Blank	zS	338	227	A-1	202
101102204270091	22	1 960	Galvaniserad	sZ	338	227	A-1	202
101102203270091	22	1 960	Galvaniserad	zS	338	227	A-1	202
101102404070091	24	1 960	Blank	sZ	402	270	A-1	240
101102403070091	24	1 960	Blank	zS	402	270	A-1	240

101102404270091	24	1 960	Galvaniserad	sZ	402	270	A-1	240
101102403270091	24	1 960	Galvaniserad	zS	402	270	A-1	240
101102504070091	25	1 960	Blank	sZ	436	293	A-1	261