



## Stållina skidlift 6x36WS-FC

### Produktinformation



**Konstruktion:** 6x36WS-FC (216-trådig)

**Märkning:** Enligt standard

**Standard:** EN 12385-8

**Fyllnadsfaktor:** 0.53

<b>Art.nr</b>	<b>Lindiameter mm</b>	<b>Stålarea mm<sup>2</sup></b>	<b>Min brottkraft kN 1570 N/mm<sup>2</sup></b>	<b>Min brottkraft kN 1770 N/mm<sup>2</sup></b>	<b>Min brottkraft kN 1960 N/mm<sup>2</sup></b>	<b>Vikt kg/100m</b>
109802806220199	28	325	418	472	522	282
109803006220199	30	390	480	542	600	324
109803206220199	32	450	547	616	682	368
109803406220199	34	499	617	696	770	416
109803606220199	36	550	692	780	864	466
109803806220199	38	620	771	869	962	520
109804006220199	40	690	854	963	1066	576
109804206220199	42	770	942	1062	1176	635
109804406220199	44	810	1033	-	-	697
109804606220199	46	915	1130	-	1410	762
109804806220199	48	980	1230	1387	1535	829
109805006220199	50	1 060	1335	1505	1666	900
109805206220199	52	1 140	1443	1627	1802	973
109805406220199	54	1 260	1577	1755	-	1 050
109805606220199	56	1 340	1674	1887	-	1 229