



## Stållina 1x7

### Produktinformation



S

Z

A

**Konstruktion:** 1x7 (7-trådig)

**Märkning:** Enligt standard

**Standard:** SS 424 08 06

**Fyllnadsfaktor:** 0.78

Staglina



Art.nr	Lindiameter mm	Trådållfasthet N/mm <sup>2</sup>	Stålärea mm <sup>2</sup>	Min brottkraft kN	Ytbehandling	Lina Ø mm	Vikt kg/100m	Uppskattad leveranstid (dagar)
100100641520020	6,4	1370_1420	25	32	Starkgalvanizerad	2,12	19	10
100100642520020	6,4	1370_1420	25	32	Starkgalvanizerad	2,12	19	10
100100731520020	7,3	1370_1420	33	43	Starkgalvanizerad	2,44	26	10
100100732520020	7,3	1370_1420	33	43	Starkgalvanizerad	2,44	26	10
100100921520020	9,2	1370_1420	52	68	Starkgalvanizerad	3,08	41	10
100100922520020	9,2	1370_1420	52	68	Starkgalvanizerad	3,08	41	10
100101061520020	10,6	1370_1420	68	89	Starkgalvanizerad	3,52	54	10
100101062520020	10,6	1370_1420	68	89	Starkgalvanizerad	3,52	54	10
100101211520020	12,1	1370_1420	89	116	Starkgalvanizerad	4,02	70	10
100101212520020	12,1	1370_1420	89	116	Starkgalvanizerad	4,02	70	10