


Ställina 1x7

Produktinformation

S Z A

[... Read more](#)



Konstruktion: 1x7 (7-trådig)

Märkning: Enligt standard

Standard: SS 424 08 06

Fyllnadsfaktor: 0.78

Staglina



Stållina 1x7

Lyfttabell

Art.nr	Lindiameter mm	Tråd hållfasthet N/mm ²	Ytbehandling	Rope lay	Min brottkraft kN	Stålarea mm ²	Smörjning	Vikt kg/100m
100101061520020	10,6	1 370/1 420	Starkgalvaniserad	S	89	68	Dry	54
100101062520020	10,6	1 370/1 420	Starkgalvaniserad	Z	89	68	Dry	54
100101211520020	12,1	1 370/1 420	Starkgalvaniserad	S	116	89	Dry	70
100101212520020	12,1	1 370/1 420	Starkgalvaniserad	Z	116	89	Dry	70
100100641520020	6,4	1 370/1 420	Starkgalvaniserad	S	32	25	Dry	19
100100642520020	6,4	1 370/1 420	Starkgalvaniserad	Z	32	25	Dry	19
100100731520020	7,3	1 370/1 420	Starkgalvaniserad	S	43	33	Dry	26
100100732520020	7,3	1 370/1 420	Starkgalvaniserad	Z	43	33	Dry	26
100100921520020	9,2	1 370/1 420	Starkgalvaniserad	S	68	52	Dry	41
100100922520020	9,2	1 370/1 420	Starkgalvaniserad	Z	68	52	Dry	41