

Stållina 6x19S-FC

Produktinformation



Konstruktion: 6x19S-FC (114-trådig)

Märkning: Enligt standard


Standard: EN 12385-4

Fyllnadsfaktor: 0.49

Redskap



Telfer/ Travers



Tornkran



Art.nr	Lindiameter mm	Stålärea mm ²	Min brottkraft kN 1770 N/mm ²	Min brottkraft kN 1960 N/mm ²	Min brottkraft kN 2160 N/mm ²	Vikt kg/100m
101100604250170	6	13,8	21	23.1	-	13
101100654250170	6,5	16,2	24.7	27.3	-	15,2
101100704250170	7	18,8	28.6	31.7	-	18
101100753250170	7,5	21,6	32.9	36.4	40.1	20

101100804250170	8	24,6	37.4	41.4	-	23
101100904250170	9	31,1	47.3	52.4	-	29
101101003250170	10	38,4	58.4	64.7	-	36
101101104250170	11	46,5	70.7	78.3	-	43
101101204250170	12	55,3	84.1	93.1	-	52
101101303250171	13	64,9	98.7	109	-	61
101101404250171	14	75,3	114	127	-	70
101101504250171	15	86,4	131	146	-	81
101101603250171	16	98,3	150	166	-	92
101101804250171	18	124	189	210	-	116
101102004250171	20	154	234	259	-	144
101102204250171	22	186	283	313	-	174
101102404250171	24	221	336	373	-	207
101102603250171	26	260	395	437	-	243
101102804250171	28	301	458	507	-	281
101103004250171	30	346	526	582	-	323
101103204250171	32	393	598	662	-	368
101103404250171	34	444	675	748	-	415
101103604250171	36	498	757	838	-	465