



## Stållina 6x19M-WSC liktrådig

### Produktinformation



**Konstruktion:** 6x19M-WSC (133-trådig)

**Märkning:** Enligt standard

**Standard:** EN 12385-4

**Fyllnadsfaktor:** 0.53

**RCN:** 04

Redskap



Vinschlina



Staglina



Jordbruk och boskap



Art.nr	Lindiameter mm	Stålärea mm <sup>2</sup>	Min brottkraft kN 1960 N/mm <sup>2</sup>	Min brottkraft kN 1770 N/mm <sup>2</sup>	Vikt kg/100m
101101804270201	-	135	230	-	123
101100204250200	2	1,67	2.84	2.56	1,52
101100304250200	3	3,76	6.39	5.77	3,43
101100404250200	4	6,69	11.4	10.3	6,1
101100504250200	5	10,5	17.7	16	9,53
101100554250200	5,5	12,6	21.5	19.4	12
101100604250200	6	15	25.5	23.1	13,7
101100654250200	6,5	17,7	30	27.1	16
101100704250200	7	20,5	34.8	31.4	18,7
101100804250200	8	26,8	45.4	41	24,4
101100904250200	9	33,9	57.5	51.9	30,9
101101004250200	10	41,8	71	64.1	38,1
101101104250200	11	50,6	85.9	77.5	46,1
101101204250200	12	60,2	102	92.3	54,9
101101304250200	13	70,6	120	108	64,4
101101404250201	14	81,9	139	126	74,7
101101504250201	15	94,1	160	144	85,7
101101604250201	16	107	182	164	97,5
101101804250201	18	135	-	208	123
101102004250201	20	167	284	256	152