Stållina Dyform 8 PI

Produktinformation



Dyform 8 PI is a high performance compacted single layer constructed rope which incorporates a plastic layer between the 8 outer strands.

- Improved bending fatigue performance
- Stable rope construction
- Diameter stability, requirement of multi-layered spooling

... *Read more*

Fyllnadsfaktor: 0,68
Tolerans Ø: 0% to +5%

CERTEX Svenska AB
info@certex.se
08-758 00 10

© November 2026 - All Rights Reserved

Stållina Dyform 8 PI

Lyfttabell

Art.nr	Lindiameter mm	Trådhållfasthet N/mm²	Ytbehandling	Rope lay	Min brottkraft kN	Smörjning	Vikt
103101104270859	11	1 960	Galvaniserad	sZ	110	SupplierStandard	57
103101304990859	13	1 960	Galvaniserad	sZ	150	SupplierStandard	79
103102004990859	20	1 960	Galvaniserad	sZ	353	SupplierStandard	188
103104003270859	40	1 960	Galvaniserad	zS	1 410	SupplierStandard	74
103104004270859	40	1 960	Galvaniserad	sZ	1 410	SupplierStandard	754
103104206270856	42	1 960	Galvaniserad	zZ	1 560	C	831

CERTEX Svenska AB
info@certex.se
08-758 00 10
© November 2026 - All Rights Reserved