



Wire Rope Clip with Forged Bridge POWERTEX PCTB

Produktinformation



The Powertex Wire Rope Clip with Forged Bridge PCTB is suitable for suspending static loads and single-use lifting operations. Available in sizes from 6 to 40 mm, this wire rope clip is designed and tested in accordance with the EN 13411-5B standard, ensuring compliance and reliability in every use.

Product benefits

- **Safety compliance:** These wire rope clips comply with EN 13411-5(Type B) standards, meeting stringent safety and quality requirements.
- **Superb grip:** The bridge features distinctive friction ridges that increase friction between the bridge and the wire rope, ensuring a secure grip where the rope makes contact with the bridge.
- **High load capacity:** When correctly mounted, the assembly can withstand up to 80% of the rope's minimum breaking load (MBL), providing robust and reliable performance.
- **Compatibility:** Designed for use with six-stranded right-hand lay ropes in 6x19 (M) and 6x36 classes and right-hand ordinary lay wire rope in 8x19 class up to 1960 N/mm², with fiber core and steel core.
- **Durable finish:** 7-10 mm Dacromet, >10 mm are hot-dip galvanized
- **Full traceability:** Every Wire Rope Clip is marked with Powertex or PX branding, Size, and a traceability code, ensuring traceability to the production lot and raw materials.

Art.nr	Benämning	Lindiameter mm	Storlek	Gänga	Antal lås vid lyft*	Moment Nm	A mm	C mm	D mm	F mm	G mm	H mm	I mm	J mm	Vikt kg	Uppskattad leveranstid (dagar)
121101100230	PCTB-11	11	7/16	1/2-13 UNC	3	88	58	28	30,5	47,3	30,5	12,1	26	50	0,32	10

Ritning & mått

