

Stållina 6x36WS-FC

Produktinformation



Konstruktion: 6x36WS-FC (216-trådig)

Märkning: Enligt standard

Standard: EN 12385-4


Fyllnadsfaktor: 0.5

RCN: 09

Redskap



Telfer/ Travers



Art.nr	Lindiameter mm	Stålarea mm ²	Min brottkraft kN 1960 N/mm ²	Min brottkraft kN 2160 N/mm ²	Min brottkraft kN 1770 N/mm ²	Vikt kg/100m
101100804270341	8	25,2	41.4	45.6	-	24
101100904270341	9	31,8	52.4	57.7	-	30
101101004270341	10	39,3	64.7	71.3	-	37
101101104270341	11	47,6	78.3	86.2	-	44

101101204270341	12	56,6	93.1	103	-	53
101101304270341	13	66,4	109	120	-	62
101101404270341	14	77	127	140	-	72
101101504250341	15	88,4	146	-	131	82,6
101101604270341	16	101	166	182	-	94
101101704270341	17	114	187	-	-	106
101101804270341	18	127	210	231	-	119
101101904270341	19	142	233	257	-	132
101102004270341	20	157	259	285	-	147
101102104250341	21	173	-	-	258	162
101102204270341	22	190	313	345	-	178
101102404270341	24	226	373	411	-	211
101102604270341	26	266	437	482	-	248
101102804270341	28	308	507	559	-	288
101103004270341	30	354	582	642	-	330
101103204270341	32	402	662	730	-	376
101103404270341	34	454	748	-	-	424
101103604270341	36	509	838	924	-	476
101103804270341	38	567	934	1029	-	530
101104004270341	40	629	1035	1140	-	587
101104204270341	42	693	1141	1257	-	647
101104404270341	44	761	1252	1380	-	711
101104604250341	46	832	-	-	1236	777

101104804270341	48	905	1490	1642	-	846
101105004250341	50	983	-	-	1460	918
101105204270341	52	1 063	1749	1927	-	992
101105604270341	56	1 232	2028	2235	-	1 151
101106004270341	60	1 415	2328	2566	-	1 321