



Kaus 3400

Produktinformation

Utförande: Gjutna.

Standard: DIN 3091

Material: GTW40.

Märkning: Enligt standard

Ytbehandling: Obehandlade.

Standard: DIN 3091

Anmärkning: Levereras obearbetade, bearbetning offereras.

Art.nr	Lindiameter mm	A obearbetad	A min bearbetad	A max bearbetad	B,	C,	L	Vikt kg/100st	Ca. levtid (arbetsdagar)
123100800070	8	14	17	20	40	15	66	18	3
123101000070	10	18	21	25	50	17,5	82	32	10
123101200070	12	21	24	30	60	20	98	52	3
123101400070	14	25	29	35	70	23,5	114	80	3
123101600070	16	28	32	40	80	26	130	90	3
123101800070	18	31	35	45	90	28,5	145	121	3
123102000070	20	35	40	50	100	31	161	161	3
123102200070	22	38	43	55	110	33,5	177	211	3
123102400070	24	41	46	60	120	36	193	271	3
123102600070	26	44	49	65	130	39,5	209	355	3
123102800070	28	47	52	70	140	42	224	420	3
123103200070	32	53	58	80	160	47	256	630	10
123103600070	36	59	65	90	180	53	288	884	3
123104000070	40	65	71	100	200	58	320	1 100	10
123104400070	44	70	76	110	220	63	352	1 500	10
123104800070	48	76	82	120	240	69	384	2 000	10

Ritning & mått

