



Schackel 9000 – oklassad

Produktinformation

Schackel för allmänt bruk.

Ytbehandling: Elförzinkad.

Anmärkning: Ej för lyft.

| Art.nr | Pin diameter | b1 mm | d1 mm | d2 mm | d3 mm | h1 mm | Vikt kg | Ca. levtid (arbetsdagar) |
|--------------|--------------|----------|----------|----------|----------|----------|------------|--------------------------|
| 490100500200 | 5 | 10 | 5 | 10 | 5 | 20 | 0,016 | 3 |
| 490100600200 | 6 | 12 | 6 | 12 | 6 | 24 | 0,032 | 3 |
| 490100800200 | 8 | 16 | 8 | 16 | 8 | 32 | 0,07 | 3 |
| 490101000200 | 10 | 20 | 10 | 19 | 10 | 40 | 0,134 | 3 |
| 490101100200 | 11 | 22 | 11 | 21 | 11 | 44 | 0,176 | 10 |
| 490101300200 | 13 | 25 | 12 | 24 | 12 | 48 | 0,25 | 3 |
| 490101400200 | 14 | 28 | 14 | 27 | 14 | 56 | 0,36 | 10 |
| 490101600200 | 16 | 32 | 26 | 31 | 16 | 64 | 0,53 | 3 |
| 490101900200 | 19 | 38 | 19 | 38 | 20 | 80 | 0,92 | 10 |
| 490102200200 | 22 | 44 | 22 | 43 | 22 | 85 | 1,4 | 10 |
| 490102500200 | 25 | 50 | 25 | 49 | 25 | 100 | 2,15 | 3 |
| 490102800200 | 28 | 56 | 28 | 54 | 28 | 116 | 3,4 | 10 |
| 490103200200 | 32 | 64 | 32 | 62 | 32 | 129 | 4,6 | 10 |

Ritning & mått

